



## ASTM - NFPA - FIRSTLINE GLOVE SIZING STANDARDS COMPARISON

GLOVE SIZE	ASTM D3578 / D6319 STANDARD			EN 455-2:2000 STANDARD			FIRSTLINE LATEX				FIRSTLINE NITRILE			
	Palm Width		Length	Palm Width		Length	Palm Width			Length	Palm Width			Length
	Tol +/- 10	Range	Min mm	Tol +/-10	Range	Min mm	Tol +5	Avg	Range	Min mm	Tol +5	Avg	Range	Min mm
<b>XS</b>	70	60-80	240	≤80	≤80	240	72	77	72-77	250 or 300	75	78	75-80	240 or 300
<b>S</b>	80	70-90		80	70-90		82	85	82-87		85	88	85-90	
<b>M</b>	95	85-105		95	85-105		92	95	92-97		95	98	95-100	
<b>L</b>	111	101-121		110	100-120		105	107	105-110		105	108	105-110	
<b>XL</b>	N/A	N/A		≥110	≥110		110	112	110-115		110	114	110-115	
<b>2XL</b>	N/A	N/A		N/A	N/A		115	118	115-120		118	122	118-123	
<b>3XL</b>	N/A	N/A	↓	N/A	N/A	↓	120	123	120-125	↓	126	129	126-131	↓